


# PP-Series High Purity Pleated Polypropylene

PP-Series High Purity Pleated Polypropylene Filter Cartridges provide a high area, 100% polypropylene element for removal of fine or coarse particulate from fluid streams.

The pleated depth media is encapsulated in an integral, continuous length, thermally-bonded structure for cleanliness, pressure tolerance, and chemical inertness. Offered in both absolute-rated (up to 99.98% retention) and nominally-rated (90% retention) grades in all end configurations. Manufactured in a clean-room environment to maintain high standards of purity and cleanliness.

Commonly used in food/beverage and chemical applications as a final filter or prefiltration stage.

## Flow Rate vs Pressure Drop



\*All data is based on absolute rated medias. Nominally rated medias will result in a pressure drop reduction of approximately 10%

### Typical Applications

- Food & Beverage
- Deionized Water
- R.O. Pre-Filtration
- Process Water
- Fine Chemicals
- Plating Chemicals
- Wastewater
- Pharmaceutical Prefiltration



## **Construction Materials**

Filtration Media	Polypropylene
Support Media	Polypropylene
End Caps	Polypropylene
Center Core	Polypropylene
Outer Support Cage	Polypropylene
O-Rings/Gaskets	.Buna, EPDM, Silicone,
Teflon® Enca	apsulated Viton®, Viton®,
Teflon	® Encapsulated Silicone

### Sanitization/Sterilization

Filtered Hot Water	80°C for 30 min.
Steam Sterilization	121°C for 30 min.,
	multiple cycles

Chemicals: Cartridges are compatible with most chemical sanitizing agents.

Note: Stainless steel insert option required for all cartridges being hot water sanitized or steam sterilized.



NSF Certification applies for use only with drinking water. Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified. Product options denoted with asterisk (\*) are not included in the Certification.

### **Dimensions**

#### Length:

10 to 40 inches (25.4 to 101.6 cm) nominal

#### **Outside Diameter:**

2.70 inches (7.0 cm) nominal

## **Operating Conditions**

Change Out $\Delta P$ (recommende	<b>d)</b> 35 PSID
Temperature (max)	176°F (80°C)
Differential Pressure (max)	60 PSID (4.1 bar)
	at 68°F (20°C)

## **Toxicity**

All polypropylene components meet the specifications for biological safety per USP Class VI - 121°C for plastics.

# **Food Safety Compliance**

Materials of construction comply with FDA regulations for food and beverage contact use as detailed in the US Code of Federal Regulations, 21CFR. Materials used to produce filter media and hardware are deemed safe for use in contact with foodstuffs in accordance with EU Directives 2002/72/EC, 1935/2004, and/or 10/2011.

## **Ordering Information**

PP	Rating (µ)	Retention	Length	С	End Cap Style	O-Rings/Gaskets	Adders
	0.2	A = Absolute	10" (25.4 cm)		2 = DOE Flat Gasket	B = Buna	CS = 316SS Compression Spring
	0.45	N = Nominal	20" (50.8 cm)		3 = 222 w/ Fin	E = EPDM	FG = Glass Reinforced PP Core *
	1.0		30" (76.2 cm)		4 = 222 w/ Flat Cap	S = Silicone	HP = Heavy Poly Core ★
	2.0		40" (101.6 cm)		5 = 222 w/ Spring	T = Teflon® Encapsulated Viton®*	I = Stainless Steel Insert
	5.0				6 = 226 w/ Flat Cap	V = Viton®*	R = 18 Megaohm Rinse
	10.0				7 = 226 w/ Fin	Z = Teflon® Encapsulated Silicone *	SS = Stainless Steel Core
	20.0				8 = 226 w/ Spring		
	40.0				16 = 213 Internal O-Ring		
					28 = 222 3-tabs w/ Fin		

DISCLAIMER: Filtration data presented is representative of performance observed in controlled laboratory testing. It is not given as a warranty, specification or statement of fitness for use. Specific performance can vary widely depending on contaminant

DS\_PP\_190918

